

## Durable chemical-resistant gloves with heightened grip, ideal for outdoor application

- **Enhanced grip:** AlphaTec™ 58-530B chemical gloves' ANSELL GRIP™ coating means less force is needed for handling wet or oily parts
- **Elevated comfort:** Their black acrylic inner liner enhances comfort while facilitating outdoor application
- **Advanced defenses:** These AlphaTec™ gloves' bonded construction, with a coating polymer that doesn't penetrate the liner in manufacture, ensures EN 374 Type A chemical protection
- **Improved durability:** They also achieve ANSI/ISEA 105-2024 ABRASION LEVEL 5 and EN ABRASION LEVEL 3
- **Specialized protection:** Beyond chemical protection, they possess EN 407 contact heat level 1, preventing workplace injuries
- **Augmented dexterity:** AlphaTec™ 58-530B PPE gloves' light 7-gauge design makes them more dexterous, for maneuverable hand protection



### Industries

- Automotive
- Metal fabrication
- Food Processing

### Applications

- Metalworking & assembly operations
- Body painting including surface inspection
- Applying sealers, touching up
- Changing tools and dies
- Handling application & cleaning tools
- Warehousing of raw materials
- Loading and unloading trucks and vehicles
- Filling, blending and charging of raw materials
- Transferring liquids and solids
- Transferring liquids and solids between vessels and tanks and process equipment
- Supervision of running operation
- Handling outgoing goods: cans, vessels, bulkpack and cartons
- Opening furnaces draining pumps valves or lines and crackers BTX process
- Food Processing

# AlphaTec™

## 58-530B

Unique combination of grip and chemical resistance

### Key Features

- ♦ **ANSELL GRIP™ Technology:** Less force needed to grip wet or oily parts
- ♦ **Black acrylic liner:** Comfortable and ideally colored for outdoor usage
- ♦ **Bonded construction:** No liner penetration and heightened dexterity

### Vulcanization Chemical Accelerators

- Zinc Diethyldithiocarbamate

Only a very small number of users may be sensitive to this ingredient(s) and hence may develop irritant and/or allergic contact reactions.

### Technologies



**ANSELL GRIP™**  
Ansell Grip Technology



### Performance Standards

ANSI/ISEA 105-2024



EN388: 2016



3122A

EN 407



XIXXXX

EN ISO 374-1:2016



AJKLOPT

EN ISO 374-5:2016



0493



### Specifications

| BRAND   STYLE     | DESCRIPTION                                                                                  | GAUGE | SIZE               | Length (MM/INCHES) | COLOR | PACKAGE                               |
|-------------------|----------------------------------------------------------------------------------------------|-------|--------------------|--------------------|-------|---------------------------------------|
| AlphaTec™ 58-530B | Liner Material: Acrylic<br>Coating Material: Nitrile<br>Featured Technology:<br>ANSELL GRIP™ | 7     | 7, 8, 9,<br>10, 11 | 290 / 11.4         | Grey  | • 6 pairs/polybag; 12 polybags/carton |

#### Europe, Middle East & Africa Region

Ansell Healthcare Europe NV  
Riverside Business Park  
Blvd International, 55  
1070 Brussels, Belgium  
T: +32 (0) 2 528 74 00  
F: +32 (0) 2 528 74 01

#### North America Region

Ansell Healthcare Products LLC  
111 Wood Avenue South,  
Suite 210  
Iselin, NJ 08830, USA  
T: +1 800 800 0444  
F: +1 800 800 0445

#### Latin America & Caribbean Region

Ansell Commercial Mexico S.A. de C.V.  
Blvd. Bernardo Quintana No. 7001-C,  
Q7001 Torre II,  
Suites 1304, 1305 y 1306,  
Col. Centro Sur, c.p. 76079  
Queretaro, Qro. Mexico  
T: +52 442 248 1544 / 248 3133

#### Canada

Ansell Canada Inc.  
105, rue Lauder  
Cowansville (Québec)  
J2K 2K8, Canada  
T: 1 800 363-8340  
F: 1 888 267-3551

Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending:  
[www.ansell.com/patentmarking](http://www.ansell.com/patentmarking) © 2025 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

**Ansell**